

Mechanical interlocking for reversing starter for lateral mounting with each one auxiliary contact (1 NC per contactor) Size S0, S2, S3 !  
 Phased-out product! Successor is SIRIUS 3RA2



Product brand name	SIRIUS
Product designation	Mechanical locking device
Design of the product	for reversing starter size S0/S2/S3, can be mounted laterally

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

[www.siemens.com/ic10](http://www.siemens.com/ic10)

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA1924-2B>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA1924-2B>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA1924-2B>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA1924-2B&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA1924-2B&lang=en)

### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RA1924-2B/char>

### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA1924-2B&objecttype=14&gridview=view1>

last modified:

01/16/2020