

EazyVolt

Article number: 626000721



Recommended accessories



EVH-I holster
626000620
see page 24



Extra probe tips 2-4 mm
626006024
see page 24



Extra protection points (GS38)
626006028
see page 24

Voltage tester

The EazyVolt is a reliable **7-in-1** automatic voltage tester up to 750 V, with the following functions:

- Measuring AC voltage
- Measuring DC voltage
- Phase detection
- Continuity
- Phase rotation
- RCD test by phase-earth (once charged)
- Selftest by switch

Features

Fully automatic

- Flashlight/torch by ultra bright LED
- 3 Phase rotation by 2 probes
- Selectable probe tips 2 - 4 mm
- Waterresistant (IP65)
- Fail safe (no battery for VAC/DC measurement)
- Schuko compliant (19 mm)
- 1 hand operation by IP2X
- IP2X

Including

- + Batteries
- + Manual

Specifications

Function	Range
Voltage	12...750 VAC/DC
RCD check	
Continuity	

Specifications	
Auto power on	>12 VAC/DC
LED resolution	12, 24, 50, 120, 230, 400, 750 V
Voltage detection	Automatic
Drop proof	1 meter
Response time	< 0.1 s
Frequency range	45...65 Hz
Continuity	< 200 K Ω
Over voltage protection	CAT III 1000 V / CAT IV 600 V
Supply	2x AAA, 1.5 V battery
IP protection	IP 65
Standard	EN 61010-1 / -031, EN 61243-3, EN 60529, EN 61557-7/ -10/ -1, EN 61326, EN 55011
Dimensions	239 x 68 x 29 mm
Weight	220 g (incl. batteries)

EazyVolt *Plus*

Article number: 626000722



Recommended accessories



EVH-I holster
626000620
see page 25



Extra probe tips 2-4 mm
626006024
see page 25



Extra protection points (GS38)
626006028
see page 25

Voltage tester

The EazyVolt is a reliable **9-in-1** automatic digital voltage tester up to 750 V, with the following functions:

- Measuring AC voltage
- Measuring DC voltage
- Resistance
- Frequency
- Phase detection
- Continuity and diode
- Phase rotation
- RCD test by phase-earth (once charged)
- Selftest by switch

Features

- Fully automatic
- Flashlight/torch by ultra bright LED
- 3 Phase rotation by 2 probes
- Selectable probe tips 2 - 4 mm
- Dual display for VAC and Hz
- Water proof (IP65)
- Fail safe (no battery for VAC/DC measurement)
- Schuko compliant (19 mm)
- 1 hand operation by IP2X

Including

+ Batteries

+ Manual

Specifications

Function	Range
Voltage	6...750 VAC ($\pm 1.3\% + 5d$) 6...750 VDC ($\pm 1.0\% + 2d$)
Frequency	1...999 Hz ($\pm 0.3\% + 5d$)
Resistance	0...2 K Ω ($\pm 2\% + 2d$)
RCD check	

Specifications	
Overvoltage protection	CAT III 1000 V / CAT IV 600 V
Supply	2x AAA, 1.5 V battery
LCD Resolution	1 V
Drop proof	1 meter
Voltage detection	Automatic
Response time	< 0.1 s/BAR < 2 s/RDG
Continuity	< 200 K Ω
Auto power on	> 12 VAC/DC
IP protection	IP65 pending
Standard	EN 61010-1 / -031, EN 61243-3, EN 60529, EN 61557-7/ -10/ -1, EN 61326, EN 55011
Dimensions	239 x 68 x 29 mm
Weight	235 g (incl. batteries)