



EN 61010-1  
EN 61326-1  
EN 61010-2-032



■ UT205A



■ UT206A

### SPECIFICATIONS



| Specifications          | Range                        | Best Accuracy |           |
|-------------------------|------------------------------|---------------|-----------|
| Model                   |                              | UT205A        | UT206A    |
| AC Current(A)           | 400A/1000A                   | ±(1.5%+5)     | ±(1.5%+5) |
| AC Voltage(V)           | 4V/40V/400V/600V             | ±(1.2%+5)     | ±(1.2%+5) |
| DC Voltage(V)           | 400mV/4V/40V/400V/600V       | ±(0.8%+1)     | ±(0.8%+1) |
| Resistance(Ω)           | 400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ | ±(1%+2)       | ±(1%+2)   |
| Frequency (Hz)          | 10Hz~10MHz                   | ±(0.1%+3)     | ±(0.1%+3) |
| Temperature (°C)        | -40 °C~1000 °C               |               | ±(2%+8)   |
| Features                |                              |               |           |
| Display Count           |                              | 4000          | 4000      |
| Auto Range              |                              | ✓             | ✓         |
| Jaw Capacity            |                              | 40mm          | 40mm      |
| Duty Cycle              | 0.1%~99.9%                   | ✓             |           |
| Diode                   |                              | ✓             | ✓         |
| Auto Power Off          |                              | ✓             | ✓         |
| Continuity Buzzer       |                              | ✓             | ✓         |
| Low Battery Indication  |                              | ✓             | ✓         |
| Data Hold               |                              | ✓             | ✓         |
| Relative Mode           |                              |               | ✓         |
| LCD Backlight           |                              | ✓             | ✓         |
| Full Icon Display       |                              | ✓             | ✓         |
| Input Impedance for DCV | Around 10MΩ                  | ✓             | ✓         |

### GENERAL CHARACTERISTICS

|                              |                                                                                         |
|------------------------------|-----------------------------------------------------------------------------------------|
| Power                        | 9V Battery(6F22)                                                                        |
| LCD Size                     | 37mm × 18mm                                                                             |
| Product Color                | Red and Grey                                                                            |
| Product Net Weight           | 350 g                                                                                   |
| Product Size                 | 236mm × 97mm × 40 mm                                                                    |
| Standard Accessories         | UT205A-Battery, Test Lead<br>UT206A-Battery, Test Lead, Point Contact Temperature Probe |
| Standard Individual Packing  | Gift Box, Carrying Bag, English Manual                                                  |
| Standard Quantity Per Carton | 20 PCs                                                                                  |
| Standard Carton Measurement  | 530mm × 360mm × 385mm (0.073 CBM Per Standard Carton)                                   |
| Standard Carton Gross Weight | 17 Kg                                                                                   |

Power Parameters Pty. Ltd.  
83 Northern Road  
Heidelberg West Vic 3081  
Freecall: 1800 623 350    Freefax: 1800 067 263  
www.parameters.com.au    power@parameters.com.au